

MPTA-B2c-2011

STANDARD PRACTICE FOR
SHEAVE/PULLEY BALANCING



MPTA STANDARD

Contributors

B&B Manufacturing, Inc.	LaPorte, IN	www.bbman.com
Baldor Dodge Maska	Greenville, SC	www.baldor.com
Carlisle Transportation Products, Inc.	Miamisburg, OH	www.carlislebelts.com
Custom Machine & Tool Co., Inc.	Hanover, MA	www.cmtco.com
Diamond Precision Products A Division of Saelens Corporation	Johnson Creek, WI	www.diamondprecision.com
Emerson Power Transmission	Maysville, KY	www.emerson-ept.com
Gates Corporation	Denver, CO	www.gates.com
Goldens' Foundry & Machine Co.	Columbus, GA	www.gfmco.com
H. Neuman & Company	Schiller Park, IL	www.hneuman.com
Lovejoy, Inc.	Downers Grove, IL	www.lovejoy-inc.com
Martin Sprocket & Gear, Inc.	Arlington, TX	www.martinsprocket.com
Maurey Manufacturing Corp.	Holly Springs, MS	www.maurey.com
TB Wood's Incorporated	Chambersburg, PA	www.tbwoods.com
Torque Transmission	Fairport Harbor, OH	www.torquefans.com
Veyance Technologies, Inc. Goodyear Engineered Products	Fairlawn, OH	www.goodyear.com/PTP

Disclaimer

This publication is presented for the purpose of providing reference information only. You should not rely solely on the information contained herein. Mechanical Power Transmission Association (MPTA) recommends that you consult with appropriate engineers and /or other professionals for specific needs. Again, this publication is for reference information only and in no event will MPTA be liable for direct, indirect, incidental or consequential damages arising from the use of this information.

Abstract

This standard defines the balance tolerances to be used with all transmission sheaves/pulleys with or without grooves or teeth.

Copyright Position Statement

MPTA publications are not copyrighted to encourage their use throughout industry. It is requested that the MPTA be given recognition when any of this material is copied for any use.

Table of Contents

SECTION	PAGE
1. Forward	3
2. Scope	4
3. Types of Balancing	4
3.1. One-Plane Balancing (static)	
3.2. Two Plane Balancing (dynamic)	
4. Units of Unbalance	4
5. One-Plane Balancing (static)	5
6. Two-Plane Balancing (dynamic)	5
7. Table 1: MPTA balancing formulae for one-plane balancing (static)	7
8. Table 2: MPTA balancing formulae for two-plane balancing (dynamic) (use when operating speed is unknown)	8
9. Table 3: MPTA balancing formulae for two-plane balancing (dynamic) (use when operating speed is known)	9

1. Foreword

This foreword is provided for informational purposes only and is not to be construed to be part of any technical specification.

When a body rotates, centrifugal forces act upon each particle in that body, tending to impel the particles away from the axis of rotation. If the mass of a rotating body is unevenly distributed about its axis of rotation, these centrifugal forces are unbalanced and there is a tendency for the entire body to rotate about its center of gravity. These unbalanced forces may cause vibration, noise, poor bearing life, and high fatiguing stresses. To minimize these forces, it is necessary to alter the mass distribution to make the center of mass concentric with the axis of rotation. That is known as Balancing the Product.

Suggestions for the improvement of, or comments on this publication are welcome. They should be mailed to Mechanical Power Transmission Association, 5672 Strand Court, Suite 2, Naples, FL 34110 on your company letterhead.

2. Scope

This standard applies to sheaves/pulleys for rubber V-Belts covered under RMA/MPTA publications IP-20 (Classical), IP-21 (Double -V), IP-22 (Narrow), IP-23 (Light Duty), IP-24 (Synchronous Belts), IP-26 (V-Ribbed), and IP27 (Curvilinear Toothed Synchronous Belts).

3. Types of Balancing

3.1. One-Plane Balancing (static)

A one-plane balance is the recommended balance for all products.

3.2. Two Plane Balancing (dynamic)

A two-plane balance is recommended only in certain cases where the product face width is relatively large and the operational speed relatively fast, or where balance is considered very critical. A two-plane balance is an option which must be specified.

4. Units of Unbalance

Unbalance may be measured in various ways and unbalance units may take several forms. This standard will list four:

Measure	English Units	Metric Units
Mass at Rim O.D.	ounce	Gram
Unbalance	ounce-inch	gram-millimeter
Eccentricity *	Inch	Millimeter
Balance Quality (G)	inch/sec	millimeter/sec

* Eccentricity is the displacement from the center of mass to the center of rotation. This term should not be confused with vibration displacement measurements

5. One-Plane Balancing (static)

5.1. The balance quality values are based on the allowable peripheral speed of cast iron (6,500 ft/min or 33m/sec).

5.2. Since it is impractical to attain a good balance level on sheaves/pulleys which are light in mass, the required lower limit of balance level is broken into two categories:

5.2.1. Standard or general purpose products (RMA/MPTA IP 20, 22 and 24) when the mass is under 11 pounds (5 Kg mass).

5.2.2. Fractional Horsepower or Light Duty products such as RMA/MPTA Standard IP-23 (2L, 3L, 4L and 5L) are excepted when the mass is under 22 pounds (10 Kg mass).

5.3. Refer to Table 1 for the balancing formulae.

6. Two-Plane Balancing (dynamic)

6.1. When considering two-plane balance, it is necessary to determine when two-plane balancing is recommended and the unbalance limits.

6.2. To determine whether two-plane balancing is recommended, perform the following calculation:

Formula #1

$$RPM = \frac{15,500}{\sqrt{D \times F}}$$

Where: D is the Diameter in inches
F is the Face Width in inches

OR

Formula #2

$$RPM = \frac{25.4 \times 15,500}{\sqrt{D \times F}}$$

Where: D is the Diameter in millimeters
F is the Face Width in millimeters

6.3. The resultant RPM is the maximum recommended operating RPM for a sheave or pulley with a one-plane balance. If the sheave or pulley is to be operated at a higher RPM, a two-plane balance is recommended.

6.4. When two-plane balancing is recommended, the formulae given in Table 2 or Table 3 should be applied.

6.4.1. When operating speed is not known, use Table 2.

6.4.2. When operating speed is known, refer to Section 6.6.

6.4.3. The two-plane balance quality is based on a peripheral rim speed of 6,500 FPM or 33m/sec for cast iron and 10,000 FPM or 50.8 m/sec for ductile iron.

WARNING: When belt speeds exceed 6,500 feet per minute, special materials must be used. Consult your manufacturer for special design requirements.

6.5. Since it is impractical to maintain a constant balance quality of smaller products, cast iron products less than 57.6 pounds (26.2 Kg) and ductile iron products less than 88.7 pounds (40.3 Kg) are balanced to a lesser quality.

6.6. When products will knowingly be operated below their maximum speed limits, the formulae given in Table 3 may be used. These formulae will provide for a balance quality equal to those given in Table 2, but require less correction because of the lower operating speeds.

Table 1, MPTA balancing formulae for one-plane balancing (static)

English Units D = Product OD (in.) M= Product Mass (lb.)	Light Duty Pulleys Under 22 lbs.	Standard Pulleys Under 11 lbs.	Light Duty 22 lbs or More Standard Duty 11 lbs or More
ounce @ Rim	0.352	0.176	0.016 x M
ounce-inch	0.176 x D	0.088 x D	0.008 x M x D
e (inch)	$\frac{0.011 \times D}{M}$	$\frac{0.0055 \times D}{M}$	0.005 x D
G (inch/sec.)	$\frac{28.6}{M}$	$\frac{14.3}{M}$	1.30
Metric Units D = Product OD (mm) M = Product Mass(kg)	Light Duty Pulleys Under 10 kg.	Standard Pulleys Under 5 kg	Light Duty 10 kg or More Standard Duty 5 kg or More
g @ Rim	10	5	M
g-mm	5.0 x D	2.5 x D	$\frac{(M \times D)}{2}$
e (mm)	$\frac{0.005 \times D}{M}$	$\frac{0.0025 \times D}{M}$	0.0005 x D
G (mm/sec)	$\frac{330}{M}$	$\frac{165}{M}$	33.0

Table 2, MPTA balancing formulae for two-plane balancing (dynamic)
(use when operating speed is unknown)

English Units D = Product OD (in.) M = Product Mass (lb.)	Cast Iron Products $V_{\max} = 6,500 \text{ FPM}$ or 33 m/sec		Ductile Iron Products $V_{\max} = 10,000 \text{ FPM}$ or 50.8 m/sec	
	All Products Less Than 57.6 lb	All Products 57.6 lb or More	All Products Less Than 88.7 lb	All Products 88.7 lb or More
ounce @ Rim (1)	0.088	$0.0015 \times M$	0.088	$0.001 \times M$
ounce-inch (1)	$0.044 \times D$	$0.00075 \times D \times M$	$0.044 \times D$	$0.0005 \times D \times M$
e (inch) (2)	$\frac{0.0055 \times D}{M}$	$0.000095 \times D$	$\frac{0.0055 \times D}{M}$	$0.00062 \times D$
G (inch/sec.) (2)	$\frac{14.3}{M}$	0.248	$\frac{22.0}{M}$	0.248
Metric Units D = Product OD (mm) M = Product Mass (kg)	All Products Less Than 26.2 Kg	All Products 26.2 Kg or More	All Products Less Than 40.3 Kg	All Products 40.3 Kg or More
g @ Rim (1)	2.5	$0.095 \times M$	2.5	$0.062 \times M$
g-mm (1)	$1.25 \times D$	$0.0475 \times M \times D$	$1.25 \times D$	$0.031 \times M \times D$
e (mm) (2)	$\frac{0.0025 \times D}{M}$	$0.000095 \times D$	$\frac{0.0025 \times D}{M}$	$0.000062 \times D$
G (mm/sec) (2)	$\frac{165}{M}$	6.3	$\frac{254}{M}$	6.3

(1) Values given for each correction plane.

(2) Values for entire product

Table 3, MPTA balancing formulae for two-plane balancing (dynamic)
(use when operating speed is known)

English Units D = Product OD (in.) M = Product Mass (lb.) (a) V = Rim Speed (FPM)	All Products Less Than 57.6 lb	All Products 57.6 lb or More
ounce @ Rim (1)	0.088	$\frac{10 \times M}{V}$
ounce-inch (1)	0.044 x D	$\frac{5 \times D \times M}{V}$
e (inch) (2)	$\frac{0.0055 \times D}{M}$	$\frac{0.62 \times D}{V}$
G (inch/sec.) (2)	$\frac{0.0022 \times V}{M}$	0.248
Metric Units D = Product OD (mm) M = Product Mass (kg) (b) V = Rim Speed (m/sec)	All Products Less Than 26.2 Kg	All Products 26.2 Kg or More
g @ Rim (1)	2.5	$\frac{3.15 \times M}{V}$
g-mm (1)	1.25 x D	$\frac{1.575 \times D \times M}{V}$
e (mm) (2)	$\frac{0.0025 \times D}{M}$	$\frac{0.00315 \times D}{V}$
G (mm/sec) (2)	$\frac{5 \times V}{M}$	6.3

(a) Speed (FPM) = 0.262 x D x RPM

(b) Speed (m/sec) = 0.000052 x D x RPM

(1) Values given for each correction plane.

(2) Values given for entire product.

END OF DOCUMENT